

DRYING OVEN

For Welding Electrodes and Submerged Arc Welding Fluxes



- Reliable Ovens which works hour after hour, day after day the same faithful consistency.
- Temperature Control :
Provided with thermostat control for precise setting of drying temperature required for various types of electrodes.
- Flawless Welds :
Totally dry welding consumables yield radiographic quality welds.



ADOR WELDING LIMITED
Central Marketing Office

L. B. S. Marg, Bhandup (W), Mumbai - 400 078. INDIA Tel.: 22 2596 2564 / 77, 2596 0285 / 88
Fax : 22 2596 6562 E-mail : cmo@adorians.com Website : www.adorwelding.com



ADOR WELDING LIMITED

ELECTRODE & FLUX DRYING OVEN

Salient Features:

- Heavy duty drying ovens for welding electrode & submerged arc welding fluxes.
- Robust constructions.
- Heavy duty metallic body.
- User friendly.
- Uniform heating of charged materials.
- Heavy duty thermostats for accurate temperature controls throughout range.

Technical Specifications:

MODELS	ADORPORT	ADORPORT 110V/220V	ADORDRY-I	ADORDRY-II	ADORDRY-III	ADORFLUX
INPUT						
Voltage	230V AC	110V / 220V AC	230V AC	230V AC	230V AC	415V AC
Current (Amps)	2	4/2	7.5	10	20	10
Phase	1 PHASE	1 PHASE	1 PHASE	1 PHASE	1 PHASE	3 PHASE
Frequency	50 Hz	50 Hz	50 Hz	50 Hz	50 Hz	50 Hz
Watts	0.5 KW	0.5KW	1.75KW	2.25KW	4.5KW	12KW
OUTPUT						
Temperature	50°C - 250°C	50°C - 250°C	50°C-250°C	50°C-350°C	50°C-500°C	50°C-400°C
GENERAL SPECIFICATIONS						
Capacity	About 4 kg. of 450 mm electrodes	About 4 kg. of 450 mm electrodes	About 25 kg. of 450 mm electrodes	About 25 kg. of 450 mm electrodes	About 25 kg. of 450 mm electrodes	About 100 kg. of flux
Working Space	80 mm dia. X 445 mm depth (Approx.)	80 mm dia. x 445 mm depth (Approx.)	440 x 450 x490mm(HWD) Height(Approx.)	440 x 450 x490mm(HWD) Height(Approx.)	440 x 450 x490mm(HWD) Height(Approx.)	600 x 600 x750mm(HWD) Height(Approx.)
No.of Shelves	-	-	FIVE	FIVE	FIVE	SIX
Air Circulation	Natural Convection	Natural Convection	Natural Convection	Natural Convection	Natural Convection	Forced Air
Temp. Control	THERMOSTAT	THERMOSTAT	THERMOSTAT	THERMOSTAT WITH ELECTRONIC CONTROLLER	THERMOSTAT WITH ELECTRONIC CONTROLLER & DIGITAL TEMPERATURE INDICATOR	

Backed by our dedicated customer care package.

Contact Authorised Distributor:

India's Welding Power House

ADOR WELDING LIMITED
Central Marketing Office

L. B. S. Marg, Bhandup (W), Mumbai - 400 078. INDIA Tel.: +91-22-2596 2564 / 77, 2596 0285 / 88

Fax : +91-22-2596 6562 E-mail : cmo@adorians.com Website : www.adorwelding.com

