

ADVANCES IN WELDING CONSUMABLES FOR OIL, GAS AND POWER SECTORS - PART I

INTRODUCTION

Welding is an important and critical activity in fabrication, construction and erection of any component, machinery and plant. Oil, Gas and Power industries are no exception to this. Over the years, these industries have witnessed several technological advances which have enabled them to operate more efficiently. These technological advances have also resulted in the use of several newer materials as well stringent quality requirements which ensure safe and efficient operation. Welding technology has also grown hand in hand with these developments and today, we have a number of welding processes, techniques, equipment and consumables to meet these requirements. While developments in all these four areas are very important, the consumable area is very vital and critical, as the weld metal will remain in service and has to match the service behavior of the base material. So in designing the weld metal or the consumable a lot of effort is put in to ensure its service life, producing a defect free weld joint. In this article we will highlight the developments that have taken place in consumables for welding of carbon steels.

CONSUMABLES FOR CARBON STEELS

Carbon steels are the most widely used materials in these industries. The common consumables like E6013, E7018 (SMAW), ER70S2 (GTAW), ER70S6 (GMAW), EL8, EM12K, and EH14(SAW) have been standardized with respect to their properties and performance and are being used for many carbon steel applications in these industries for many years now. However several special consumables have been developed to meet specific application requirements.

Consumables for NACE applications

In the Oil and Gas industry a number of components are exposed to hydrogen sulphide and sour gas environments resulting in stress corrosion cracking. Weld metals operating in these environments are normally tested to ensure that they will stand these service conditions. NACE specifications TM 01 77 and TM02 84 specify suitable tests to



- India's First Double operator welding set with multiprocess welding capabilities and conforming to latest CPCB norms for Noise & Emission level
- Ideal for heavy duty fabrication & site applications
- Versatile applications, suitable for manual and semi-automatic welding process for cross country, in-plant pipeline welding applications
- Highly reliable even in hostile site conditions
- Big savings in fuel, resulting in longer runs before next re-fueling
- Specially proven with cellulosic (6010 & 7010 types) and other special types of electrodes
- Super Silent Operation

determine the behavior of the weld metal. The details of the weld metals meeting these requirements are indicated in **Table1**. With the availability of these consumables, several tons of carbon steels have been successfully welded in this industry.

Table 1: Consumables meeting NACE requirements.

Property	E7018-1	ER70S2 SPL	EH10K + FLUX
C	0.05	0.05	0.06
Mn	1.2	1.2	1.3
Si	0.25	0.5	0.25
S	0.008	0.008	0.012
P	0.010	0.010	0.012
UTS Kg/mm2	540	--	55
YS Kg/mm2	430	--	43
%El	26	--	23
CVN impact -30C	60J	--	75J
SSCC TM0177	OK	OK	OK
HIC TM0284	OK	OK	--

Moisture resistant and vacuum packed electrodes

Moisture is a detrimental factor in welding. Higher moisture content in the environment, shielding gas and flux, base material can introduce more hydrogen in the weld metal. Hydrogen is not a desired element in the weld metal since it makes the steel brittle. So in carbon and low alloy steel welding, extra care is exercised to limit hydrogen in coating. When electrodes and fluxes are opened from their containers and exposed to atmosphere they absorb moisture and the amount of hydrogen absorption is dependent on the relative humidity of the environment at that time. In order to ensure that the electrodes, fluxes are dry at the time of usage, they are normally re-dried, particularly low hydrogen consumables. Most of the fabricators use this procedure during welding and satisfactory results are obtained.

However there are many occasions when re-drying may not be possible. In order to meet this requirement electrodes have been developed which resist moisture pick up. These electrodes are designated with a suffix 'R' indicating they are moisture resistant electrodes. These electrodes are tested for moisture resistance by subjecting them to special tests as indicated in **Table 2**.

Table 2: Moisture resistant electrodes

AWS	As received coating moisture	After exposure to 80% RH for 9 hrs at 27C
E7018	0.6%	Not specified

CELWEL
AWS Class: 6010/7010/8010



- All-position electrodes including vertical down
- Ideal for cross-country pipeline welding (stove pipe welding technique or 6 GR applications)
- Deep penetrating forceful arc
- Consistency in performance batch after batch, welder-friendly
- Covers the entire range of API pipe grades (X42 to X70) including root filling and capping runs
- Moisture controlled
- Test certificates with every batch & full support for Welding Procedure Qualification
- Approved by leading agencies i.e. ABS, DNV, LRS, TOYO, PDIL, etc.
- International-quality packing (TIN packed)

**ADOR Institute of
Welding Technology**



**Course for Quality Assurance
& Control of Welding (QA-1)**
17th - 20th Jan. 2011

E7018R

0.3%

0.4%

In order to preserve these electrodes in the factory packed condition till usage, they are vacuum packed which ensures quality at the time of usage. Another advantage of vacuum packing is that these electrodes don't require re-drying like conventional low hydrogen electrodes.

There are a number of applications in Oil & Gas industries where re-baking is not feasible and the welding environment is always with high relative humidity. The development of vacuum packed moisture resistant electrodes is a great boon specifically for these applications.

Weld metals with enhanced toughness requirements

Weld metal toughness is an important property. It is usually measured with the CVN impact test which specifies a minimum value for the average impact strength at specified temperatures. While these values are the basic minimums, having a higher value is preferred by the fabricators which can to some extent take care of any procedural variations during welding and still produce a tough weld metal. Hence specifications today, call for minimum impact values which are much higher than the standard values. Some specification details are given in **Table 3**. This illustrates the stringent quality standards to which the weld metal has to conform.

Table 3: Specific impact requirements

Condition	Value J
AWS standard	27
No value less than	40
Minimum average value	40
Welding under specified heat input conditions	40

Apart from this, weld metals are today required to meet CTOD value; CTOD is a fracture mechanics test to ensure toughness of the material in the presence of a running crack. While the routine specifications do not talk about this, requirements in the Oil & Gas industries specify this. A sample requirement is indicated in **Table 4**.

Table 4: CTOD values specified weld metals

AWS classification	Electrode size	CTOD values (required min 0.25 mm)
E 7018-1	2.5	0.75
	3.2	1.08
	4	0.83

AWS now specifies a separate 'J' designation for an E71T1 flux cored wire which can meet the impact properties at minus 40C.

Hands on training for
Welders / Operators

Visit AWL Stall No. F-23 at
National Expo -2 (Steel-
Power-Cement – Mining) at
Science College ground, G.
E., Raipur during 16th to 19th
Dec. 2010

Our New Toll Free
No. 1-800-233-1071

For Welding &
Cutting Equipment,
Service & Spares

Pipe welding electrodes

For pipe welding traditionally the use of cellulosic types, like E6010, has been in practice for a very long time. The use of this electrode is normally restricted to lower strength levels and for higher strength levels such as at 70000 psi, special pipe welding electrodes like E7010P1 are to be used. Electrodes are available for higher strength levels also. These are specially made for vertical down welding of pipes, (popularly referred to as stove pipe welding) particularly the root pass where penetration is of great importance. **Table 5** gives details of these types of consumables. These grades are available now indigenously. Even low hydrogen electrodes specially designed for pipe welding are available and are included in the specifications.

Table 5: Pipe welding electrodes (Typical where not mentioned)

Property	E6010	E7010 P1
C	0.2	0.2
Mn	1.2	1.2
Si	1.0 max	0.6
Ni	0.3 max	1.0 max
Cr	0.2 max	0.3 max
Mo	0.3 max	0.5 max
V	0.08 max	--
S	0.03 max	0.03 max
P	0.03 max	0.03 max
UTS KG/MM2	44	50
YS KG/MM2	34	42
CVN AT -30C	27 J	27 J

CONCLUSION

Oil, Gas and Power industries offer a number of challenges for welding by constantly using improved and newer materials. This has been the constant factor fuelling the development of a host of new and modified consumables to suit the application and also the service condition. Thanks to these cooperative efforts, today we have a wide spectrum of welding consumables meeting many service requirements. In Part II of this article, we will discuss advances in consumables for welding of alloy steels and stainless steels; we will also describe special test requirements for these consumables.

Ador Welding Ltd. consumables for carbon steels in Oil, Gas and Power industries and tests performed.

AWS CODE	PROCESS	AWL PRODUCT NAME	NACE TEST	C.T.O.D TEST AT (-10 DEG C)
E 7018-1	SMAW	TENALLOY HH SPL	DONE	N.A.
E 7018-1	SMAW	TENALLOY S PLUS	DONE	DONE
E 7018 -1	SMAW	TENALLOY Z PLUS	DONE	N.A.
E 6010	SMAW	CELWEL 60	DONE	N.A.
E 7010 G	SMAW	CELWEL 70 G	DONE	N.A.
E 8010 G	SMAW	CELWEL 80 G	DONE	N.A.

To know more about the special requirements and availability of welding consumables in the Oil, Gas and Power sectors please contact us at cmo@adorians.com, or visit us at www.adorwelding.com



Project Engineering Solutions



ADOR Institute of Welding Technology



Welding & Cutting Solutions



Centre for Engineering Excellence



WELDERS TO THE NATION
ADOR WELDING LIMITED
 (formerly known as Advani - Oerlikon Ltd.)



www.adorwelding.com

cmo@adorians.com

Contact us