

Welding Consumable : Statement of Fact

Project: Supplementary list of Welding consumables

Client: Ador Welding Limited, Silvasa plant, India Office: Mumbai

Client's Order Number: -- Date: 10 July 2023

Order Status: Complete

Inspection Dates

First: **05 May 2023** Final: **04 July 2023**

This statement is issued to Ador Welding Limited, Silvasa plant, India to certify that the undernoted welding consumable is recommended for entry in the supplementary list of certified welding consumables in accordance with ASME Section II Part C, SFA 5.1, E7016-1 H4R specification of the year 2021. This statement is issued on the basis of satisfactory test results on the test coupons prepared on 05/05/2023 and subsequently tested on 04/07/2023. Welding consumables is manufactured by Ador Welding Limited, Silvasa plant, India.

Description:-

Consumable Name : TENALLOY 16 SPL Size : 4.0 and 5.0mm

SFA Classification : SFA / AWS 5.1 E7016-1 H4R

Result of the Test :

Size	4.0 mm	5.0mm					
0.2%Proof Stress	485	458					
(MPa) (Min.: 400MPa)							
UTS (MPa) (Min.:	564	539					
490MPa)							
% Elongation (Min.	31	32					
22%)							
Hydrogen test	Acceptable	Acceptable					
Chemical	Acceptable	Acceptable					
Radiography	Acceptable	Acceptable					
Fillet (H,V,OH)	Acceptable	Acceptable					
Charpy V notch Impact	test at -45 Deg C.	Acceptable value:					
27J average and 20J individual							
1	96*	64*					
2	66	56					
3	78	48					
4	80	50					
5	42*	22*					
Average value (J)	75	51					



Note: ' * ' - Indicates highest and lowest discarded values.

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.

Diffusible Hydrogen Test:

	Size	Actual	Actual	Actual Result	Average	Max	
		Result (1)	Result (2)	(3)			
Millilitres per 100 grams of Weld Metal	4.0 mm	3.638	3.709	3.581	3.643	4	
Millilitres per 100grams	5.0 mm	3.892	3.797	3.864	3.851	4	
of Weld Metal							

Moisture Test:

	Size	Actual Result	Max
Moisture (% by Weight)	4.0 mm	0.166 %	0.3 %
Moisture (% by Weight)	5.0 mm	0.191 %	0.3 %

Chemical Analysis - Size 4.0 X 450 mm

	% C	% Cr	% Ni	% Mo	%Mn	% Si	% P	% S	%V	% Mn+Cr+Mo+V+Ni
Range	0.15	0.20	0.30	0.30	1.60	0.75	0.035	0.035	0.08	1.74
	Max	Max	Max	Max	Max	Max	Max	Max	Max	Max
Result	0.086	0.034	0.021	0.006	1.39	0.32	0.015	0.006	0.008	1.45

Chemical Analysis - Size 5 X 450 mm

	% C	% Cr	% Ni	% Mo	% Mn	% Si	% P	% S	%V	%Mn+Cr+Mo+V+Ni
Range	0.15	0.20	0.30	0.30	1.60	0.75	0.035	0.035	0.08	1.74
	Max	Max	Max	Max	Max	Max	Max	Max	Max	Max
Result	0.089	0.034	0.021	0.006	1.31	0.27	0.016	0.006	0.007	1.38

Refer Radiography Report No: 420, results found acceptable.

For diffusible Hydrogen AM23/02326-1, dated 30/06/2023 & AM23/02326-2, dated 30/06/2023, Moisture Test report AM23/02326-1, dated 30/06/2023 & AM23/02326-2, dated 30/06/2023.

The works of above manufacturer were inspected at the location stated and found in satisfactory order. The process of manufacture including supervision, quality control and record keeping were of adequate standard and storage condition and facilities were found to be satisfactory as well.

Statement is Valid until 31 March 2024.



Surveyor to Lloyd's Register Marine and Offshore India LLP

a member of the Lloyd's Register group.

